

Permatex, Inc.
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924
 International Emergency: 813-348-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: 101H COPPER SPRAY-A-GASKET .25PT
Item No: 80696
Product Type: Sealant

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Percent	ACGIH 8 Hr. TWA:	OSHA 8 Hr. TWA:
ACETONE 67-64-1	60-70	500 ppm TWA; 1188 mg/m ³ TWA	1000 ppm TWA; 2400 mg/m ³ TWA
ACRYLONITRILE-BUTADIENE POLYMER 9003-18-3	10-20	Not Listed	Not Listed
PHENOLIC RESIN 25085-75-0	10-20	Not Listed	Not Listed
COPPER 7440-50-8	1-10	1.0 mg/m ³ (dust and mist); 0.2 mg/m ³ (fumes)	1.0 mg/m ³ (dust and mist); 0.1 mg/m ³ (fumes)

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye, skin and respiratory irritation. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage (sometimes referred to as "solvent" or "painter's syndrome"). Symptoms include fatigue, concentration difficulties, anxiety, depression, rapid mood swings, and short-term memory loss. Aspiration hazard if swallowed.

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation.

Signs and Symptoms of Exposure: Excessive overexposure may cause giddiness, dizziness, headache, nausea and in extreme cases, unconsciousness and respiratory depression. Overexposure may cause eye and skin redness, difficulty breathing and vomiting.

Ingredients	Percent	NTP:	ACGIH Carcinogens	IARC:
ACETONE 67-64-1	60-70	Not known	A4 - Not Classifiable as a Human Carcinogen	Not known

Medical Conditions Recognized as Being Aggravated by Exposure: Preexisting pulmonary and dermatological disorders

4. FIRST AID MEASURES

Ingestion: If swallowed, do NOT induce vomiting. Give victim two glasses of water, Call a physician immediately. Never give anything by mouth to an unconscious person.

Inhalation: If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin Contact: Remove contaminated clothing. Wash area with soap and water. If irritation persists, seek medical attention.

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C): -4 degrees F. Method: Tag Closed Cup

Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.

Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

Hazardous Products Formed by Fire or Thermal Decomposition: Irritating vapors. Metal oxide fumes,

Unusual Fire/Explosion Hazards: Closed containers may rupture or explode when exposed to extreme heat. Keep containers cool.

Lower Explosive Limit: 2.0
Upper Explosive Limit: 13.0

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage: Store away from heat, sparks or open flame. Do not store at temperatures above 120 degrees F.
Handling: Use only in a well ventilated area. Vapors may accumulate readily and may ignite explosively. Wash hands before eating, drinking, chewing gum, using tobacco or using the toilet. Avoid contact with skin and eyes.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses with side shields.
Skin: Rubber or plastic gloves
Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits during the use of this product.
Respiratory Protection: An approved respirator (i.e. NIOSH, etc.) should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Dark brown liquid
Odor: SOLVENT ODOR
Boiling Point (°F): 135 degrees F.
pH: Does not apply
Solubility in Water: Partial
Specific Gravity: 0.91
VOC Content(Wt.%): 65.9 % by weight
Vapor Pressure: 400 mm Hg
Vapor Density (Air=1): 2.0
Evaporation Rate: Faster than ether

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions
Hazardous Polymerization: WILL NOT OCCUR
Incompatibilities: Strong oxidizers.
Conditions to Avoid: Do not expose to heat or store at temperatures above 120 F.
Hazardous Products Formed by Fire or Thermal Decomposition: Irritating vapors. Metal oxide fumes,

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.
US EPA Waste Number: D001 as per 40CFR 261.21

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name: Consumer Commodity (not more than one liter)
Hazard Class: ORM-D
UN/ID Number: None
Marine Pollutant: None

Product name: 101H COPPER SPRAY-A-GASKET
.25PT

Item 80696

IATA

Proper Shipping Name: Consumer Commodity (Not more than 500 ml)
Class or Division: Class 9
UN/NA Number: ID 8000

IMDG

Proper Shipping: Adhesives, Limited Quantity
Hazard Class: Class 3.2
UN Number: UN 1133

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

SARA 313 Information
COPPER

CALIFORNIA PROP 65:

WARNING: This product contains chemicals known to the State of California to cause cancer.

TSCA Inventory Status:

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 3, REACTIVITY 1

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 3, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Health and Safety Manager
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA
06106

Revision Date: 11/18/2003

Revision Number: 2

Telephone Number: 1-87-Permatex (877) 376-2839